



tourGuide **AIR**

Analogue tourGuide
with high sound quality

tourGuide AIR



Specifications

- Frequency: 500 – 960 MHz (see table)*
- Modulation: Wideband
- Latency: no latency
- Frequency response: 40Hz – 18KHz
- Dynamic range: > 80dB
- Signal to noise ratio: > 71dB
- Service coverage: indoor: up to 100m
outdoor: up to 150m
- Operating temperature: -10°C ~ 50°C
- Sync-Kit available

*Frequency & Number of available channels

MHz	No. of channels	MHz	No. of channels
500–530	300	823–832	51
510–530	200	863–865	16
794–806	120	863–870	70
806–810	30	902–928	49
812–824	120	925–937,5	125
819,1–823,1	40	944–952	80

CE; FCC

AIR Transmitter

AIR Receiver

RF output power	10mW	–
Inputs	Mic in x 1	Headphone out x 1 (32Ω)
Microphone	extern	–
Buttons	Channel selector, Volume	
On/off button	Power on/off & Mute	Power on/off
Battery	LI-Polymer (1300mAh /3,7V)	
Operating time	12 h	18 h
Charging source	DC 5V Micro USB	
Charging time	approx. 6 h	
LCD display	Channel, battery indicator, volume, mute	
Antenna	solid	with headphones
Dimension (W/H/D)	40x82,6x12 mm (Antenna length not included)	
Weight	49 g	
Color	Silver	Rubin Red

Charger & transportation

	Dual-slot charger	Charger bag	Charger case	Drawer/ Trolley
Number of slots	2	12	35	60/70
Power supply	DC 5V 1A	DC 5V 4A	DC 5V 10A	DC 19V 6.3A
Dimension (W/H/D) in mm	68x42x68	332x130x104	440x270x140	595x220x600 820x220x430
Weight	121g	1,2 kgs	3 kgs	14/12 kgs